

MATERIAL SAFETY DATA SHEET

CHAINLICK (Aerosol)

1. **IDENTIFICATION**:

COMPANY: ITW INDIA LIMITED ADDRESS: PLOT NO 34 – 37, PHASE -2,

APIIC, PASHAMMYLARAM,

MEDAK - 502 307 (35 KM FROM HYDERABAD)

INDIA.

EMERGENCY CELL No: 91-9000031515
TELEPHONE: 91 - 8455 - 224700
FAX: 91 - 8455 - 224705

PRODUCT USE: Chain Lubricant for parts and equipments

PACKAGES: Aerosol.

NFPA RATING: Health1, Flammability (Aerosol 4), Reactivity 0.

REVISION DATE: June 2011

2. HAZARDOUS INGREDIENTS:

	Wt/wt%	CAS# T	TLV	LD 50	LC 50	R-Phrases	
Heavy Normal Paraffin:	15-23%	64- 742467	7 Not avail	Not avail	Not avail	R36\38	
White Mineral Oil	8-12%	8042-47-5	Not avail	1600mg/kg	Not avail	R 41,R 51/53	
polyisobutene	45-60	9003-29-6	Not avail	>10250mg/kg	$>17000 \text{mg/m}^3$	R36/R38	
Isobutane	20-40%	75-28-5	Not Avail	1000ppm	Not Avail	R11	

3. HAZARDS IDENTIFICATION:

Important Hazards-Fire:

Flammable.

Gas/Vapor explosive with air with in explosion limits. The vapors are heavier than air, spreads along the ground.

Aerosol may explode under the affect of heat.

Environmental Hazards: Toxic to aquatic organisms. May cause long term adverse effects in aquatic environment.

POTENTIAL HEALTH EFFECTS & SIGNS AND SYMPTONS OF EXPOSURE: Skin Contact: Repeated exposure may cause skin dryness or cracking

Eyes: May irritating, but does not damage eye tissue.

Inhalation: Vapors may cause dizziness and nausea.

Ingestion: Not intestinal irritation significant in small (mouthful) amounts but in large quantities it may cause nausea,

vomiting and gastro intestinal irritation

4. FIRST AID:

Skin Contact: Remove contaminated clothing. Wash exposed areas with soap and water.

Eyes: Rinse carefully under upper and lower eyelids using plenty of water for at least 10 min.

Inhalation: Remove to fresh air if dizzy or nauseated. In case of loss of consciousness, give artificial

Respiration.

Ingestion: Do not induce vomiting. Accidental ingestion of a single mouthful is not expected to cause

significant harm. Rinse mouth with water.

NOTE: In all severe cases, contact physician immediately.

5. FIRE HAZARD:

Conditions of flammability:

Flash point: >93 °C (Pensky Marten closed cup)

Flammable limits in air: 1.6% to 10%

Extinguishing media: Carbon Dioxide, foam, water, dry chemicals Special fire fighting procedures: Keep containers cool with water spray.

Hazardous combustion products: Smoke, soot, oxides of carbon

Unusual fire hazards: Aerosol cans may burst at temperatures over 50 °C and add to existing fire.

Special Protective equipment Full protective clothing and self containing breathing apparatus.

for fighters:

6. ACCIDENTAL RELEASE MEASURES:

Personal Precautions:

Personal Protection Equipment must be worn. See Section 8.

Methods for Cleaning up:

on Soil:

Prevent product from entering drains \surface water\ground water.

Remove sources of ignition.

Mop up or sweep up with absorbent (For disposal, see Section 13)

7. HANDLING AND STORAGE:

Handling: Ensure good ventilation.

Do not spray on a naked flame or any incandescent material.

Do not pressurize ,cut ,heat or weld containers(empty product containers may contain product

esidue)

Do not handle, store or open near an open flame, sources of heat or sources of ignition.

Do not smoke.

Storage: Avoid proximity or contact with hot surfaces, flames or sparks.

Store in dry ,cool ,well ventilated area.

Keep container tightly closed.

Protect from sunlight and do not expose to temperature exceeding 50 0 C.

Keep away from heat.

Keep away from all sources of ignition.

Avoid breathing vapors. Avoid eye contact.

Avoid repeated or prolonged skin contact.

Avoid breathing spray mist.

Packaging:

-General Do not pierce or burn, even after use.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION:

Recommended Engineering: When using, do not eat ,drink or smoke.

Controls None, unless sprayed. Use where ventilation will carry spray mist away from occupied

areas.

Personal protection:

Respiratory protection: Ensure good ventilation.

High vapor concentration: gas mask, filter A.

In case of insufficient ventilation wear suitable respiration equipment. Respirator with filter if sprayed in enclosed unventilated space.

Skin and hand protection: Handle according to good industrial hygiene and safety procedures.

Appropriate protective clothing and gloves.

Wear nitrile rubber gloves if hand exposure is unavoidable.

Eye protection: Wear safety glasses to protect eyes.

9. PHYSICAL PROPERTIES:

Physical and chemical properties of active product with out gas.

These are indicative values only. Please refer to product specification sheet.

Appearance: Brown color oily liquid Odor: Mild hydrocarbon

Initial boiling point: NA >93 °C Flash point; Auto ignition temperature: NA Vapor pressure: NA Oxidizing properties: NA Pour point: NA Water solubility: Insoluble Density\Sp gravity: 865 kg/m^3

10. STABILITY AND REACTIVITY:

Stable in normal conditions of use. Excess exposure to sunlight

Conditions to avoid: &Temperatures above 50 °C should be avoided Avoid proximity or contact with flames or sparks.

Incompatibility: incompatible with strong oxidizing agents

Hazardous decomposition products: Non Hazardous

Reactivity: NA

11. TOXICOLOGICAL INFORMATION

(Based on test with similar products). (Refers to active component) No toxicological information available.

Oral LD (50 rat): >2000mg\kg

Dermal LD(50 Rabbit):

Inhalation LC (50 Rat/4h):

Skin contact:

No information available.

No information available.

yes it is slightly irritant.

Eye Contact: Will cause eye discomfort, but will not injure eye tissue.

Inhalation: Avoid breathing vapors or mists.

Irritating to respiratory system.

Irritating to respiratory system.

Ingestion:

Minimal toxicity.

Skin Sensitization test:Data not available.Mutagen city and Carcinogenicity:No information available.

12. ECOLOGICAL INFORMATION

Mobility: Semi volatile, readily absorbed into the soil

Degradability: Not established.

Ecotoxicity and bioaccumulation:

No bioaccumulation potential

13 **DISPOSAL**:

Disposal of product: This product is not suitable for disposal by either landfill or via municipal sewers, drains,

natural streams or rivers.

Dispose of in a safe manner ,in accordance with local regulations

Disposal of packing: Dispose of in a safe manner ,in accordance with local regulations.

Empty aerosol cans before disposal.

Non hazardous waste as per classification in The Hazardous Wastes (Management and

Handling) Rules 1989, of CPB, India

RCRA: hazardous waste
U.S EPA Waste number: D001

14 TRANSPORTATION:

1950 Proper Shipping Name: Aerosol -ADR/RID; LQ2 2,5F Class: Label: 2.1 -Maritime Transport(IMO-IMDG): LQ=1L Class: 2.0 EMS: F-D,S-U Packing instructions; P003

Marine pollutant:

--Air Transport(ICAO/IATA):

Class: 2
Packing instructions; 203

15. **REGULATORY INFORMATION:**

TSCA: All ingredients are listed in TSCA inventory CERCLA: Reportable quantity for Acetone=5000lbs

SARA TITLE III, Section 313: Acetone California Proposition 65: Contains

EEC Labeling information:

Hazard Symbols: Highly Flammable

Irritant: Xi

Dangerous for Environment: N

Risk phrases: R11: Highly Flammable.

R38: Irritating to Skin.

R 51\53: Toxic to aquatic organisms, may cause long term adverse effects in the aquatic

Environment.

R 67: Vapors may cause drowsiness and dizziness.

Safety phrases: Pressurized container .Protect from sunlight and do not expose to temperatures exceeding 50 °C.

Do not pierces or burn after use .Do not spray on naked flame or any incandescent material l. Keep away from sources of ignition-No smoking. Keep out of reach of children. With out adequate

ventilation formation of explosive mixtures may be possible.

S23.2: Do not breathe vapor S23.4: Do not breathe spray.

S46: If swallowed seek medical advice immediately and show this container or Label.

S 51: Use only in ventilated areas.

16. **OTHER INFORMATION**:

Sources of Key data used: Raw material supplier's data sheets were used as key data sources in the preparation

Of this safety data sheet.

Risk phrases used in Sec.3:

R 20:Harmful by inhalation R22: Harmful if swallowed

R36/38: Irritating to Eyes and skin.

R51/53: Toxic to aquatic organizations, may cause long term adverse effects in the aquatic

environment.

R 65: Harmful, may cause lung damage if swallowed. R66: Repeated exposure may cause skin dryness or cracking.

R67 Vapors may cause drowsiness and dizziness.

Revision Statement: New Supersedes: Nil

The contents and format of this MSDS are in accordance with EC Commission Directive.