



CFC Free Electro Contact Cleaner



FEATURES

- Safe on Plastics
- Fast Evaporating; Leaves No Residue
- Low Odor
- Penetrating action removes oil, grease, dirt, flux, and other contaminants
- Cleans and degreases delicate precision mechanisms

APPLICATIONS

- Connectors
- Contacts
- Fluid Systems
- Magnetic Tape Heads
- Office Equipment
- Printed Circuits
- Relays & Controls
- Semiconductor Assemblies

SPECIFICATIONS AND APPROVALS

- AMS 1525B
- ASTM F-519, Type 1C
- Caterpillar
- Ford Motor Co.
- General Motors Co.
- Honda Corp.
- Inland Steel
- Kimberly-Clark
- Kodak
- Lockheed Martin DSDN H01.2101
- MIL-PRF-29608
- NSF International, K2 (Aerosol)
- NSF International, K2 (Non-Aerosol)
- Tyco Electronics

PROPERTIES

Appearance / Physical State	Gas
Odor	Solvent
Melting / Freezing Point	N/A
Boiling Point / Range	140.9°F (60.5°C)
Vapor Pressure	352.53 mm Hg @ 38°C
Partition Coefficient	>1
Percent volatile	100%
Flammability	lower: 0.6%; upper: 7%
Propellant	Carbon Dioxide
VOC Content	Aerosol: 96.2%; Bulk: 100%
Color	Clear
Flash Point	Aerosol: < 1.4°F (< -17.0°C) TCC; Bulk: < -0.4 °F (< -18.0 °C) TCC
Density	N/A
Evaporation Rate	<1
Vapor density	-3 (air = 1)
Auto-Ignition Temperature	582.8°F (306°C)
Viscosity	< 3 cSt @ 25°C
Specific Gravity	0.64 - 0.67 @ 20°C
Temperature Range	N/A
KB Value	31
Surface Tension	17.3 dynes/cm @ 77°F (25°C)

DIRECTIONS

Hold can 6-8 inches (15-20 cm) away and spray directly on surface to clean it. DO NOT USE ON ENERGIZED ELECTRICAL EQUIPMENT IN OPERATION AND ALLOW SURFACE TO DRY BEFORE RESTART.

HANDLING

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Do not re-use empty containers. Do not breathe gas. Avoid contact with skin. Avoid contact with eyes. Avoid prolonged exposure. Avoid contact with clothing. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. When using, do not eat, drink or smoke. Wash hands thoroughly after handling.

STORAGE

Level 3 Aerosol. Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122°F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS). Protect from freezing.

DISPOSAL

Waste must be disposed of in accordance with any and all applicable environmental control rules and/ or regulations.

AVAILABLE PRODUCTS

US	Part No.		Net Contents	Container Type	Units/Case	Case Weight
	Canada	Europe				
		M03105	20 L	pail	1	
		M03115	5 L	pail	1	
03116	C03116	M03116	11 wt oz / 312 g / 465 mL	aerosol	12	11 lbs
03101	C03101		1 gal / 3.78 L	pail	4	28 lbs
03105	C03105	M03105	5 gal / 18.93 L	pail	1	33 lbs
03155	C03155		55 gal / 208 L	drum	1	308 lbs



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved